



AcustiSeal™ MSDS

Material safety data sheet 11/1/2007

1. Product and Company identification

Product name: AcustiSeal™	Manufacturer: Rendered by manufacturer and released to: Acoustical Surfaces, Inc. 123 Columbia Court North -Suite 201 Chaska, MN 55318
Product type: water based acoustical sealant	
Emergency contact: 866-435-8893	

2. Composition information

Name:	CAS number:	Percent by weight:
Latex polymer	None established	25-60%
Water	7732-18-5	30-50%
CaCO3	471-34-1	30-80%

This product does not contain hazardous or carcinogenic components Reportable under OSHA Hazard Communication Standard 1910.1200

3. Hazards identification

3.1 Emergency Overview		HMIS Rating	
Appearance:	thin, light green paste	Health:	1 (slight)
Odor:	Slight characteristic latex to no odor	Flammability:	0 (minimal)
Fire Hazard	Not a Significant fire Hazard	Chronic:	0 (minimal)
3.2 Potential Health Effects			
Ingestion:	Potential irritant, do not ingest		
Inhalation	Not expected to be harmful under normal conditions of use. However, if allowed to become airborne, may cause irritation of nose, throat and lungs.		
Skin:	May cause irritation on prolonged or repeated contact or if allowed to dry on skin, brief contact is not anticipated or shown to cause irritation.		
Eyes:	May cause irritation.		
3.3 Delayed Hazards: None known to company			

4. First Aid Measures

Immediate Hazards	
Ingestion:	If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.
Inhalation	Remove to fresh air.
Skin:	In case of contact, flush with water and wash until clean. If material is noticed on skin before dry, wash prior to material drying if at all possible.
Eyes:	Immediately flush eyes with plenty of water. Call a physician if irritation persists.



5. Fire Fighting Measures

Auto ignition Temperature:	Not available
Upper/Lower Flammable Limits:	Not available
Up/Lower Explosive Limits, % by Vol:	Not applicable
Flash Point:	Not available
<i>Material is incombustible as supplied, but dried material will support combustion. In case of fire, water should be used to keep fire-exposed containers cool.</i>	

6. Accidental Release Measures

Soak up with absorbent material and remove to a chemical disposal area. Prevent entry into natural bodies of water.

7. Handling and Storage

7.1 Handling
Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Wash thoroughly after handling. Always use appropriate Personal Protective Equipment (PPE).
7.2 Storage
Keep from Freezing
Store in a cool, dry place.
Keep containers tightly closed

8. Exposure Controls/Personal Protection

8.1 Exposure limits and controls
Exposure limits: none established
8.2 Personal protection
Inhalation: Inhalation is not anticipated to be a route of exposure in normal use. If the product is to become airborne use NIOSH/MSHA approved respiratory protection equipment.
Skin: Wear latex or other water-impermeable gloves. Wear coveralls to prevent skin contact.
Eye: Wear safety glasses