Bailey 2299

Paris Frost 7020



Allagash Mist 7040



Khaki 7012



Belmont Silver 7010




Platinum 7013




Cave 7047



Baxter Beige 7011



Sherman Pewter 7024



Kennebec Blue

Bailey 2299

Specifications

| Content | 100% pre-consumer recycled polyester |
|-----------|--------------------------------------|
| Weight | 8.3 ± 0.5 oz./lin. yd. |
| Width | 66" min. useable |
| Repeat | none |
| Treatment | polyester binder |

Cleaning Code


Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Bleach Cleanable - May be cleaned with a 10% bleach-to-water solution. Rinse well after cleaning. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Acoustical Performance

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

Acoustical Performance for Panel Applications (ISO 10534-2)



| NRC of anechoic termination | 1.00 |
|--|------|
| NRC of fabric in front of anechoic termination | .95 |

Performance

| * | Colorfastness to Light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours |
|---|--|
| U | Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet |
| × | Breaking Strength (ASTM D5034) 150 lbf min. warp and 100 lbf min. fill |
| | |

Sustainability



Flammability (ASTM E84)

Class I or A



Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.

