

# RSIC-1 SI RESILIENT SOUND ISOLATION CLIP

## RSIC-1 SI Pro Series Spring Isolator

### RSIC-SI Pro Series

1/4 x 20 threaded rod to allow for several mounting systems.

This spring-type vibration isolator is currently available in 5, 10, 20, 40, 80, and 160 lb options with 1" deflection.

1. The 40# spring can support two layers of 5/8" Fire Code C with the Springs spaced at 4' x 2' (2.5# x 2 Layers x 8 square feet = 40 lbs).
2. The 80# spring can support two layers of 5/8" Fire Code C with the Springs spaced at 4' x 4' 2.5# x 2 Layers x 16 square feet = 80 lbs).
3. The 160 pound spring can support double the load or double the distance with a heavy duty Carrier Channel such as 3-5/8" x 20 gauge or heavier steel stud the spring can be at 4' x 8' OC.



RSIC-SI



RSIC-SI-CRC

Acoustical Surfaces, Inc.  
A Master Distributor for  
PAC INTERNATIONAL, INC.



**ACOUSTICAL | SURFACES, INC.**

Celebrating Over 40 Years - SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION SPECIALISTS!  
952.448.5300 | 800.448.0121 | sales@acousticalsurfaces.com | www.acousticalsurfaces.com