BeeHave 3948



BeeHave 3948

Specifications

65% pre-consumer recycled polyester 35% post-consumer recycled polyester
12.1 ± 1.0 oz./lin. yd.
54" min. useable
1.1" vertical .75" horizontal
BLOCKaide® stain repellent


Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Acoustical Performance

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

Acoustical Performance for Panel Applications (ISO 10534-2)



NRC of anechoic termination	1.00
NRC of fabric in front of anechoic termination	.95

Performance

Colorfastness to Light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet Breaking Strength (ASTM D5034)

Seam Slippage (ASTM D4034) 50 lbf min. warp and 40 lbf min. fill

> Pilling Resistance (ASTM D3511) Class 4 min.

250 lbf min. warp and 175 lbf min. fill



Flammability CA Technical Bulletin 117-2013 Section 1 ASTM E84 Class I or A



Abrasion (ASTM D4157) 75,000 double rubs min. cotton duck

Sustainability



100% recycled and recyclable
Terratex is a registronic Terratex is a registered trademark of Duvaltex

Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.



program. Additional testing of this U.L. recognized component fabric is not required on approved panels from participating manufacturers.

Guilford of Maine®