

Material Safety Data Sheet GREENchoice Heavy Duty Construction Adhesive

1. Product and company identification

CAS #	: mixture
Address	: Franklin International 2020 Bruck Street Columbus OH 43207
Contact person	: Franklin Technical Services
Telephone	: (800) 877-4583
In case of emergency	: Franklin Security (614) 445-1300
Reference number	: 3631
Product code	: 7472
Date of revision	: 3/2/2012.
Print date	: 3/30/2012.
Chemtrec (24 Hour)	: (800) 424 - 9300
Chemtrec International	: (703) 527 - 3887
Chemical family	: Adhesive.
Product use	: Construction Adhesive solvent free

2. Hazards identification

Emergency overview		
Physical state	quid. [Paste.]	
Color	ige.	
Odor	naracteristic. [Slight]	
Signal word	ARNING!	
Hazard statements	ARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION.	
Precautionary measures	o not ingest. Avoid contact with eyes, skin and clothing. Wash thoroughly after ndling.	
OSHA/HCS status	is material is considered hazardous by the OSHA Hazard Communication Stand 9 CFR 1910.1200).	dard
Routes of entry	ermal contact. Eye contact. Inhalation. Ingestion.	
Potential acute health effect		
Inhalation	posure to decomposition products may cause a health hazard. Serious effects delayed following exposure.	may
Ingestion	xic if swallowed.	
Skin	ghtly irritating to the skin. Prolonged or repeated contact can defat the skin and tation, cracking and/or dermatitis.	lead to
Eyes	ghtly irritating to the eyes. This product may irritate eyes upon contact.	
Potential chronic health effe		
Chronic effects	hown significant effects or critical hazards.	
Carcinogenicity	hown significant effects or critical hazards.	

3. Composition/information on ingredients

United States

Name	CAS number	%
oxydipropyl dibenzoate	27138-31-4	5 - 10
urea	57-13-6	1 - 5
ethanediol	107-21-1	1 - 5

Name	CAS number	%
oxydipropyl dibenzoate	27138-31-4	5 - 10
urea	57-13-6	1 - 5
ethanediol	107-21-1	1 - 5

<u>Mexico</u>

					Classification			
Name	CAS number	UN number	%	IDLH	н	F	R	Special
urea	57-13-6	Not available.	1 - 5	-	2	0	0	-
ethanediol	107-21-1	Not available.	1 - 5	-	2	1	0	-
oxydipropyl dibenzoate	27138-31-4	Not available.	5 - 10	-	2	0	0	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation	 Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion	: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Flammability of the product	: In a fire or if heated, a pressure increase will occur and the container may burst.
Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Small spill	:	Stop leak if without risk. Move containers from spill area. Dispose of via a licensed waste disposal contractor. Absorb with an inert material.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling
 Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
 Storage
 Store between the following temperatures: 4.4444 to 26.667°C (40 to 80°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to

prevent leakage. Do not store in unlabeled containers. Use appropriate containment to

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits

avoid environmental contamination.

8. Exposure controls/personal protection

urea	AIHA WEEL (United States, 5/2010).	
	TWA: 10 mg/m ³ 8 hour(s).	
ethanediol	OSHA PEL 1989 (United States, 3/1989).	
	CEIL: 50 ppm	
	CEIL: 125 mg/m ³	
	ACGIH TLV (United States, 2/2010).	
	C: 100 mg/m ³ Form: Aerosol	

Canada

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
ethanediol	US ACGIH 2/2010 AB 4/2009 BC 9/2010 ON 7/2010 QC 6/2008 US AIHA 5/2010	- - - - - -	- - 10 - - - 10	- - - - -	- - - - - 50 -	- - 20 - - 127 -	- - - - - -	- - - 50 - - -	100 100 - - 100 - - -	- - - - - -	[a] [3] [b] [a] [c] [d] [b] [e]

[3]Skin sensitization **Form:** [a]Aerosol [b]aerosol [c]Particulate [d]Vapour [e]vapour and mist

<u>Mexico</u>

Occupational exposure limits

Ingredient	Exposure limits
ethanediol	NOM-010-STPS (Mexico, 9/2000). LMPE-Pico: 100 mg/m ³

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
Engineering measures	:	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection		
Respiratory	:	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eyes	-	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Skin	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

GREENchoice Heavy Duty Construction Adhesive

8. Exposure controls/personal protection

Environmental exposure	: Emissions from ventilation or work process equipment should be checked to ensure they
controls	comply with the requirements of environmental protection legislation.

9. Physical and chemical properties

Physical state	: Liquid. [Paste.]
Flash point	: Closed cup: >93.333°C (>200°F) [Setaflash.]
Color	: Beige.
Odor	: Characteristic. [Slight]
рН	: 5
Boiling/condensation point	: 100°C (212°F)
Relative density	: 1.4
Volatility	: 25% (w/w)
Evaporation rate	: <1 (butyl acetate = 1)
VOC (less water, less exempt solvents)	: 6.6 g/l
Dispersibility properties	: Dispersible in the following materials: cold water and hot water.

10. Stability and reactivity

Chemical stability	: The product is stable.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous polymerization Incompatibility	 Under normal conditions of storage and use, hazardous polymerization will not occur. Reactive or incompatible with the following materials: acids and alkalis.

11. Toxicological information

United States

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
urea	LD50 Oral		8471 mg/kg	-
ethanediol oxydipropyl dibenzoate	LD50 Oral LD50 Oral		4700 mg/kg 3295 mg/kg	-

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
urea	Skin - Mild irritant	Human	-	72 hours 22 milligrams Intermittent	-
	Skin - Moderate irritant	Human	-	24 hours 20 Percent	-
ethanediol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Mild irritant	Rabbit	-	1 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	6 hours 1440	-

11. Toxicological information

	Skin - Mild irritant	Rabbit	-	milligrams 555 milligrams	-
0				Ū	

Conclusion/Summary

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes

Skin

: This product may irritate eyes upon contact.

<u>Sensitizer</u>

No known significant effects or critical hazards.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
ethanediol	A4	-	-	-	-	-

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

Canada

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanediol oxydipropyl dibenzoate urea	LD50 Oral	Rat	4700 mg/kg 3295 mg/kg 8471 mg/kg	-

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanediol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Mild irritant	Rabbit	-	1 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	6 hours 1440 milligrams	-
	Skin - Mild irritant	Rabbit	-	555 milligrams	-
urea	Skin - Mild irritant	Human	-	72 hours 22 milligrams Intermittent	-
	Skin - Moderate irritant	Human	-	24 hours 20 Percent	-

Conclusion/Summary

Skin

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes

: This product may irritate eyes upon contact.

Sensitizer

No known significant effects or critical hazards.

3/30/2012.

11. Toxicological information

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
ethanediol	A4	-	-	-	-	-

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

<u>Mexico</u>

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
urea ethanediol oxydipropyl dibenzoate	LD50 Oral LD50 Oral LD50 Oral	Rat	8471 mg/kg 4700 mg/kg 3295 mg/kg	- -

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
-	Skin - Mild irritant	Human	-	72 hours 22 milligrams Intermittent	-
	Skin - Moderate irritant	Human	F	24 hours 20 Percent	-
-	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Mild irritant	Rabbit	-	1 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	F	6 hours 1440 milligrams	-
	Skin - Mild irritant	Rabbit	ł	555 milligrams	-

Conclusion/Summary

Skin

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Eyes

: This product may irritate eyes upon contact.

Sensitizer

No known significant effects or critical hazards.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
ethanediol	A4	-	-	-	-	-

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

GREENchoice Heavy Duty Construction Adhesive

No known significant effects or critical hazards.

12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

United States

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
urea	Acute EC50 3910000 ug/L Fresh water	Daphnia - Daphnia magna - Neonate - <24 hours	48 hours
	Acute LC50 >1000 mg/L Marine water	Crustaceans - Chaetogammarus marinus - Young - 5 mm	48 hours
	Acute LC50 5000 ug/L Fresh water	Fish - Colisa fasciata - Fingerling	96 hours
ethanediol	Acute LC50 >100000 ug/L Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 >10000000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 8050000 ug/L Fresh water	Fish - Pimephales promelas - <=7 days	96 hours

Persistence/degradability

No known significant effects or critical hazards.

<u>Canada</u>

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
ethanediol	Acute LC50 >100000 ug/L Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 >10000000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 8050000 ug/L Fresh water	Fish - Pimephales promelas - <=7 days	96 hours
urea	Acute EC50 3910000 ug/L Fresh water	Daphnia - Daphnia magna - Neonate - <24 hours	48 hours
	Acute LC50 >1000 mg/L Marine water	Crustaceans - Chaetogammarus marinus - Young - 5 mm	48 hours
	Acute LC50 5000 ug/L Fresh water	Fish - Colisa fasciata - Fingerling	96 hours

Persistence/degradability

No known significant effects or critical hazards.

<u>Mexico</u>

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
urea	Acute EC50 3910000 ug/L Fresh water	Daphnia - Daphnia magna - Neonate - <24 hours	48 hours
	Acute LC50 >1000 mg/L Marine water	Crustaceans - Chaetogammarus marinus - Young - 5 mm	48 hours
	Acute LC50 5000 ug/L Fresh water	Fish - Colisa fasciata - Fingerling	96 hours
ethanediol	Acute LC50 >100000 ug/L Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 >10000000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 8050000 ug/L Fresh water	Fish - Pimephales promelas - <=7 days	96 hours

Persistence/degradability

No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal	: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
----------------	--

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14.	Transport	information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		-
TDG Classification	Not regulated.	-	-	-		-
Mexico Classification	Not regulated.	-	-	-		-
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG* : Packing group

15. Regulatory information

United States

HCS Classification

U.S. Federal regulations

: Toxic material

: TSCA 4(a) final test rules: sodium hydroxymethanesulphinate; biuret

TSCA 8(a) IUR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted. SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: ethanediol; urea SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No products were found.

15. Regulatory information

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	ethanediol	107-21-1	1 - 5
Supplier notification	ethanediol	107-21-1	1 - 5

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

In the state of th	Our destruction Next and the Martineer					
Not available.						
California Prop. 65						
Pennsylvania	: The following components are listed: 1,2-ETHANEDIOL					
New Jersey	: The following components are listed: ETHYLENE GLYCOL; 1,2-ETHANEDIOL					
New York	: The following components are listed: Ethylene glycol					
Massachusetts	: The following components are listed: ETHYLENE GLYCOL					
State regulations						

Ingredient name	Cancer	•	No significant risk level	Maximum acceptable dosage level

<u>Canada</u>

WHMIS (Canada)

: Class D-1B: Material causing immediate and serious toxic effects (Toxic). Class D-2A: Material causing other toxic effects (Very toxic).

Canadian lists Canadian NPRI

Canada inventory

PRI : The following components are listed: Ethylene glycol

CEPA Toxic substances

s : None of the components are listed.
 : At least one component is not listed in DSL but all such components are listed in NDSL.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

<u>Mexico</u>

Classification



International regulations

GREENchoice Heavy Duty Construction Adhesive

15. Regulatory information

0 ,		
International lists	:	Australia inventory (AICS): Not determined. China inventory (IECSC): Not determined. Japan inventory: Not determined. Korea inventory: Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined.
Chemical Weapons Convention List Schedule I Chemicals	:	Not listed
Chemical Weapons Convention List Schedule II Chemicals	:	Not listed
Chemical Weapons Convention List Schedule III Chemicals	:	Not listed

16. Other information

Label requirements Hazardous Material Information System (U.S.A.) : HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION.



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing	:	3/30/2012.
Date of issue	:	3/2/2012.
Date of previous issue	:	2/15/2012.
Version	:	2

Indicates information that has changed from previously issued version.

16. Other information

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.